



# COUNTRY COLLECTION

U P H O L S T E R Y

*Natural Leather*

## TECHNICAL DATASHEET

|                                                                                                                                                                                                                                                                                                                   | TEST METHOD<br>PRÜFVERFAHREN<br>METHOD TEST<br>MÉTODO DE PRUEBA | MEASUREMENT UNIT<br>MAßEINHEIT<br>UNIT OF MEASUREMENT<br>UNIDAD DE MEDIDA                                | GUARANTEED<br>GARANTIERT<br>INSURED<br>GARANTIZADA |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------|
| <b>BURNING BEHAVIOUR TO CIGARETTE AND MATCH FLAME</b><br><b>BRANDVERHALTEN GGÜ. ZIGARETTENGLUT UND STREICHHOLZFLAMME</b><br><b>COMPORTEMENT DE COMBUSTION DES CIGARETTES ET ALLUMETTES</b><br><b>COMPORTAMIENTO FRENTE AL FUEGO Y LLAMA</b>                                                                       | BS 5852:1979<br>BS EN 1021-1-2:2006                             | <br>FIRE<br>RETARDANT | PASS                                               |
| <b>COLOUR FASTNESS TO RUBBING   DRY 50 CYCLES</b><br><b>ABRIEBFESTIGKEIT   TROCKEN 50 ZYKLEN</b><br><b>RÉSISTANCE AUX FROTTEMENTS   A SEC 50 CYCLES</b><br><b>SOLIDEZ DEL COLOR AL FROTE   A SECO 50 CICLOS</b>                                                                                                   | UNI EN ISO 11640:1998                                           | GREY SCALE                                                                                               | ≥ 3                                                |
| <b>COLOUR FASTNESS TO RUBBING   WET 20 CYCLES</b><br><b>ABRIEBFESTIGKEIT   NASS 20 ZYKLEN</b><br><b>RÉSISTANCE AUX FROTTEMENTS   HUMIDE 20 CYCLES</b><br><b>SOLIDEZ DEL COLOR AL FROTE   MOJADO 20 CICLOS</b>                                                                                                     | UNI EN ISO 11640:1998                                           | GREY SCALE                                                                                               | ≥ 3                                                |
| <b>COLOUR FASTNESS TO RUBBING   SWEAT 20 CYCLES</b><br><b>ABRIEBFESTIGKEIT   SCHWEIß 20 ZYKLEN</b><br><b>RÉSISTANCE AUX FROTTEMENTS   SUEUR 20 CYCLES</b><br><b>SOLIDEZ DEL COLOR AL FROTE   SUDOR 20 CICLOS</b>                                                                                                  | UNI EN ISO 11640:1998<br>ISO 11641 pH8                          | GREY SCALE                                                                                               | ≥ 2                                                |
| <b>FLEXING ENDURANCE   DRY 50.000 CYCLES</b><br><b>BIEGEFESTIGKEIT   TROCKEN 50.000 ZYKLEN</b><br><b>RÉSISTANCE À LA FLEXION   A SEC 50.000 CYCLES</b><br><b>RESISTENCIA A LA FLEXIÓN   A SECO 50.000 CICLOS</b>                                                                                                  | UNI EN ISO 5402                                                 |                                                                                                          | NO DAMAGE                                          |
| <b>TEAR STRENGTH   SINGLE EDGE TEAR</b><br><b>REIßFESTIGKEIT HOSE   EINKANTENRISS</b><br><b>RÉSISTANCE AU DÉCHIREMENT   BORD UNIQUE</b><br><b>RESISTENCIA AL DESGARRO   DESGARRO SIMPLE</b>                                                                                                                       | UNI EN ISO 3377-1                                               | N                                                                                                        | ≥ 20                                               |
| <b>COLOUR FASTNESS TO ARTIFICIAL LIGHT   EXPOSITION ENERGY 16.000 kj/sqm</b><br><b>UV-BESTÄNDIGKEIT   EXPOSITIONS ENERGIE 16.000 kj/qm</b><br><b>RÉSISTANCE À LA LUMIÈRE ARTIFICIELLE   ÉNERGIE D'EXPOSITION 16.000 kj/m²</b><br><b>SOLIDEZ DEL COLOR A LA LUZ ARTIFICIAL   EXPOSICIÓN A ENERGÍA 16.000 kj/m²</b> | UNI EN ISO 105 B02 (MET.5)                                      | BLUE SCALE                                                                                               | ≥ 3                                                |

## CLEAN AND CARE RECOMMENDATIONS

EUROPEAN BOVINE ORIGIN, LIGHTLY BUFFED NATURAL GRAIN  
DISTRESSED AND SEMI-GLOSS APPEARANCE, VINTAGE LOOK  
0.8 - 1.0 mm THICKNESS | 4.8 - 5.0 sqm AVERAGE

TO REMOVE DUST USE A VACUUM CLEANER.  
AVOID EXPOSING DIRECTLY TO SUNLIGHT AND HEAT SOURCES.  
ANY STAIN, SPILLS OR SOILING SHOULD BE CLEANED UP PROMPTLY WITH A  
NEUTRAL SOAP SOLUTION USING A CLOTH IN SMOOTH CIRCULAR MOVEMENTS.  
WE DO NOT ACCEPT RESPONSIBILITY FOR ANY DAMAGE RESULTING FROM  
INAPPROPRIATE USE, CHEMICAL CLEANING OR ADDITIONAL IMPREGNATION.

## DELIVERY AND SHIPPING

4/5 DAYS DELIVERY TIME  
EXPRESS SERVICE - READY TO SHIP IN 48h  
WORLDWIDE SHIPPING AVAILABLE