



KANSAS COLLECTION

U P H O L S T E R Y

Natural Leather

TECHNICAL DATASHEET

BURNING BEHAVIOUR TO CIGARETTE AND MATCH FLAME
BRANDVERHALTEN GGÜ. ZIGARETTENGLUT UND STREICHHOLZFLAMME
COMPORTEMENT DE COMBUSTION DES CIGARETTES ET ALLUMETTES
COMPORTAMIENTO FRENTE AL FUEGO Y LLAMA

TEST METHOD
PRÜFVERFAHREN
METHOD TEST
MÉTODO DE PRUEBA

BS 5852:1979
BS EN 1021-1-2:2006

MEASUREMENT UNIT
MAßEINHEIT
UNIT OF MEASUREMENT
UNIDAD DE MEDIDA



GUARANTEED
GARANTIERT
INSURED
GARANTIZADA

PASS

COLOUR FASTNESS TO RUBBING | DRY 50 CYCLES
ABRIEBFESTIGKEIT | TROCKEN 50 ZYKLEN
RÉSISTANCE AUX FROTTEMENTS | A SEC 50 CYCLES
SOLIDEZ DEL COLOR AL FROTE | A SECO 50 CICLOS

UNI EN ISO 11640:1998

GREY SCALE

≥ 3

FLEXING ENDURANCE | DRY 50.000 CYCLES
BIEGEFESTIGKEIT | TROCKEN 50.000 ZYKLEN
RÉSISTANCE À LA FLEXION | A SEC 50.000 CYCLES
RESISTENCIA A LA FLEXIÓN | A SECO 50.000 CICLOS

UNI EN ISO 5402

NO DAMAGE

TEAR STRENGTH | SINGLE EDGE TEAR
REIßFESTIGKEIT HOSE | EINKANTENRISS
RÉSISTANCE AU DÉCHIREMENT | BORD UNIQUE
RESISTENCIA AL DESGARRO | DESGARRO SIMPLE

UNI EN ISO 3377-1

N

≥ 20

COLOUR FASTNESS TO ARTIFICIAL LIGHT | EXPOSITION ENERGY 16.000 kJ/sqm
UV-BESTÄNDIGKEIT | EXPOSITIONS ENERGIE 16.000 kJ/qm
RÉSISTANCE À LA LUMIÈRE ARTIFICIELLE | ÉNERGIE D'EXPOSITION 16.000 kJ/m²
SOLIDEZ DEL COLOR A LA LUZ ARTIFICIAL | EXPOSICIÓN A ENERGÍA 16.000 kJ/m²

UNI EN ISO 105 B02 (MET.5)

BLUE SCALE

≥ 3

CLEAN AND CARE RECOMMENDATIONS

ASIAN BOVINE ORIGIN, NATURAL GRAIN - PURE ANILINE LEATHER
PECULIAR VELVET TOUCH, VINTAGE EFFECT - FINISHED IN EUROPE
1.2 - 1.4 mm THICKNESS | 3.8 - 4.0 sqm AVERAGE

TO REMOVE DUST USE A VACUUM CLEANER.
AVOID EXPOSING DIRECTLY TO SUNLIGHT AND HEAT SOURCES.
ANY STAIN, SPILLS OR SOILING SHOULD BE CLEANED UP PROMPTLY WITH A
NEUTRAL SOAP SOLUTION USING A CLOTH IN SMOOTH CIRCULAR MOVEMENTS.
WE DO NOT ACCEPT RESPONSIBILITY FOR ANY DAMAGE RESULTING FROM
INAPPROPRIATE USE, CHEMICAL CLEANING OR ADDITIONAL IMPREGNATION.

DELIVERY AND SHIPPING

4/5 DAYS DELIVERY TIME
EXPRESS SERVICE - READY TO SHIP IN 48h
WORLDWIDE SHIPPING AVAILABLE