



MONACO COLLECTION

A U T O M O T I V E

Natural Leather

TECHNICAL DATASHEET

	TEST METHOD PRÜFVERFAHREN METHOD TEST MÉTODO DE PRUEBA	MEASUREMENT UNIT MAßEINHEIT UNIT OF MEASUREMENT UNIDAD DE MEDIDA	GUARANTEED GARANTIERT INSURED GARANTIZADA
FLAMMABILITY BRENNVERHALTEN COMBUSTIBILITÉ INFLAMABILIDAD	FMVSS 302		< 100 mm/min.
COLOUR FASTNESS TO RUBBING DRY 1500 CYCLES ABRIEBFESTIGKEIT TROCKEN 1500 ZYKLEN RÉSISTANCE AUX FROTTEMENTS A SEC 1500 CYCLES SOLIDEZ DEL COLOR AL FROTE A SECO 1500 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
COLOUR FASTNESS TO RUBBING WET 300 CYCLES ABRIEBFESTIGKEIT NASS 300 ZYKLEN RÉSISTANCE AUX FROTTEMENTS HUMIDE 300 CYCLES SOLIDEZ DEL COLOR AL FROTE MOJADO 300 CICLOS	UNI EN ISO 11640:1998	GREY SCALE	≥ 4
COLOUR FASTNESS TO RUBBING SWEAT 100 CYCLES ABRIEBFESTIGKEIT SCHWEIß 100 ZYKLEN RÉSISTANCE AUX FROTTEMENTS SUEUR 100 CYCLES SOLIDEZ DEL COLOR AL FROTE SUDOR 100 CICLOS	UNI EN ISO 11640:1998 ISO 11641 pH8	GREY SCALE	≥ 4
FLEXING ENDURANCE DRY 50.000 CYCLES BIEGEFESTIGKEIT TROCKEN 50.000 ZYKLEN RÉSISTANCE À LA FLEXION A SEC 50.000 CYCLES RESISTENCIA A LA FLEXIÓN A SECO 50.000 CICLOS	UNI EN ISO 5402		NO DAMAGE
ADHESION OF FINISH-DRY HAFTFESTIGKEIT DER ZURICHTUNG TROCKEN ADHÉRENCE DE LA FINITION À SEC ADHERENCIA DE ACABADO SECO	UNI EN ISO 11644	N/cm	≥ 4
TEAR STRENGTH SINGLE EDGE TEAR REIßFESTIGKEIT HOSE EINKANTENRISS RÉSISTANCE AU DÉCHIREMENT BORD UNIQUE RESISTENCIA AL DESGARRO DESGARRO SIMPLE	UNI EN ISO 3377-1	N	≥ 20
TENSILE STRENGTH AND ELONGATION HÖCHSTZUGKRAFT UND DEHNUNG BEI HÖCHSTZUGKRAFT RESISTANCE À LA TENSION ET L'ALLONGEMENT RESISTENCIA A LA TRACCIÓN Y ELONGACIÓN	UNI EN ISO 3376:2006	N	≥ 130
ARTIFICIAL AGEING HEIßLICHTALTERUNG VIEILLISSEMENT ARTIFICIEL ENVEJECIMIENTO ARTIFICIAL	4h at 70°C	GREY SCALE	≥ 4
COLOUR FASTNESS TO ARTIFICIAL LIGHT EXPOSITION ENERGY 16.000 kJ/sqm UV-BESTÄNDIGKEIT EXPOSITIONS ENERGIE 16.000 kJ/qm RÉSISTANCE À LA LUMIÈRE ARTIFICIELLE ÉNERGIE D'EXPOSITION 16.000 kJ/m² SOLIDEZ DEL COLOR A LA LUZ ARTIFICIAL EXPOSICIÓN A ENERGÍA 16.000 kJ/m²	UNI EN ISO 105 B02 (MET.5)	GREY SCALE	≥ 4

CLEAN AND CARE RECOMMENDATIONS

EUROPEAN BOVINE NAPPA LEATHER, SLIGHTLY CORRECTED NATURAL GRAIN
SOFT FEEL AND SILKY TOUCH WITH A SEMI-MATTE FINISH; CAR SUITABLE
1.1 - 1.3 mm THICKNESS | 4.5 - 5.0 sqm AVERAGE

TO REMOVE DUST USE A VACUUM CLEANER.

AVOID EXPOSING DIRECTLY TO SUNLIGHT AND HEAT SOURCES.

ANY STAIN, SPILLS OR SOILING SHOULD BE CLEANED UP PROMPTLY WITH A NEUTRAL SOAP SOLUTION USING A CLOTH IN SMOOTH CIRCULAR MOVEMENTS.

WE DO NOT ACCEPT RESPONSIBILITY FOR ANY DAMAGE RESULTING FROM INAPPROPRIATE USE, CHEMICAL CLEANING OR ADDITIONAL IMPREGNATION.

DELIVERY AND SHIPPING

4/5 DAYS DELIVERY TIME

EXPRESS SERVICE - READY TO SHIP IN 48h

WORLDWIDE SHIPPING AVAILABLE