



VERMONT COLLECTION

CONTRACT • AUTOMOTIVE • UPHOLSTERY

Natural Leather

TECHNICAL DATASHEET

BURNING BEHAVIOUR TO CIGARETTE AND MATCH FLAME
BRANDVERHALTEN GGÜ. ZIGARETTENGLUT UND STREICHHOLZFLAMME
COMPOTEMENT DE COMBUSTION DES CIGARETTES ET ALLUMETTES
COMPORTAMIENTO FRENTE AL FUEGO Y LLAMA

TEST METHOD
PRÜFVERFAHREN
METHOD TEST
MÉTODO DE PRUEBA

CAL TB-117 (2013, Sec.1)
BS 5852:1979
BS EN 1021-1-2:2006

MEASUREMENT UNIT
MAßEINHEIT
UNIT OF MEASUREMENT
UNIDAD DE MEDIDA



GUARANTEED
GARANTIERT
INSURED
GARANTIZADA

PASS

COLOUR FASTNESS TO RUBBING | DRY 500 CYCLES
ABRIEBFESTIGKEIT | TROCKEN 500 ZYKLEN
RÉSISTANCE AUX FROTTEMENTS | A SEC 500 CYCLES
SOLIDEZ DEL COLOR AL FROTE | A SECO 500 CICLOS

UNI EN ISO 11640:1998

GREY SCALE

≥ 4

COLOUR FASTNESS TO RUBBING | WET 250 CYCLES
ABRIEBFESTIGKEIT | NASS 250 ZYKLEN
RÉSISTANCE AUX FROTTEMENTS | HUMIDE 250 CYCLES
SOLIDEZ DEL COLOR AL FROTE | MOJADO 250 CICLOS

UNI EN ISO 11640:1998

GREY SCALE

≥ 4

COLOUR FASTNESS TO RUBBING | SWEAT 80 CYCLES
ABRIEBFESTIGKEIT | SCHWEIß 80 ZYKLEN
RÉSISTANCE AUX FROTTEMENTS | SUEUR 80 CYCLES
SOLIDEZ DEL COLOR AL FROTE | SUDOR 80 CICLOS

UNI EN ISO 11640:1998
ISO 11641 pH8

GREY SCALE

≥ 4

FLEXING ENDURANCE | DRY 50.000 CYCLES
BIEGEFESTIGKEIT | TROCKEN 50.000 ZYKLEN
RÉSISTANCE À LA FLEXION | A SEC 50.000 CYCLES
RESISTENCIA A LA FLEXIÓN | A SECO 50.000 CICLOS

UNI EN ISO 5402

NO DAMAGE

FINISH ADHESION | DRY
HAFTUNG DER OBERFLÄCHENBEHANDLUNG | TROCKEN
ADHÉSION DU FILM | A SEC
ADHERENCIA DE ACABADO | A SECO

UNI EN ISO 11644

N/cm

≥ 2

TEAR STRENGTH | SINGLE EDGE TEAR
REIßFESTIGKEIT HOSE | EINKANTENRISS
RÉSISTANCE AU DÉCHIREMENT | BORD UNIQUE
RESISTENCIA AL DESGARRO | DESGARRO SIMPLE

UNI EN ISO 3377-1

N

≥ 20

COLOUR FASTNESS TO ARTIFICIAL LIGHT | EXPOSITION ENERGY 16.000 kJ/sqm
UV-BESTÄNDIGKEIT | EXPOSITIONS ENERGIE 16.000 kJ/qm
RÉSISTANCE À LA LUMIÈRE ARTIFICIELLE | ÉNERGIE D'EXPOSITION 16.000 kJ/m²
SOLIDEZ DEL COLOR A LA LUZ ARTIFICIAL | EXPOSICIÓN A ENERGÍA 16.000 kJ/m²

UNI EN ISO 105 B02 (MET.5)

BLUE SCALE

≥ 4

CLEAN AND CARE RECOMMENDATIONS

EUROPEAN BOVINE ORIGIN, LIGHTLY BUFFED NATURAL GRAIN
ATTRACTIVE AND VERY NATURAL LIGHT SHINY EFFECT
1.2 - 1.4 mm THICKNESS | 4.8 - 5.0 sqm AVERAGE

TO REMOVE DUST USE A VACUUM CLEANER.
AVOID EXPOSING DIRECTLY TO SUNLIGHT AND HEAT SOURCES.
ANY STAIN, SPILLS OR SOILING SHOULD BE CLEANED UP PROMPTLY WITH A
NEUTRAL SOAP SOLUTION USING A CLOTH IN SMOOTH CIRCULAR MOVEMENTS.
WE DO NOT ACCEPT RESPONSIBILITY FOR ANY DAMAGE RESULTING FROM
INAPPROPRIATE USE, CHEMICAL CLEANING OR ADDITIONAL IMPREGNATION.

DELIVERY AND SHIPPING

4/5 DAYS DELIVERY TIME
EXPRESS SERVICE - READY TO SHIP IN 48h
WORLDWIDE SHIPPING AVAILABLE